

AN3C4A - BOLT, MACHINE, NEW SURPLUS, SOLD PER EACH, NSN: 5306-00-

150-9528, NIIN: 1509528

## **Description**

## **AN3C4A - BOLT, MACHINE**

NSN: 5306-00-150-9528, NIIN: 1509528

New Surplus, Sold Per Each

A machine bolt is a heavy-duty fastener with a hexagonal head and a fully or partially threaded shank, designed for securing two or more components together.

## **Specifications**

Head Style: Hexagon

Surface Treatment: Passivate

Material: Steel

**Fastener Length**: 0.531" *Nom* **Grip Length**: 0.125" *Nom* 

Head Height: 0.109" Min - 0.141" Max

Tensile Strength Min: 125000 Pounds Per Square Inch

Width Between Flats: 0.365" Min - 0.377" Max

Features Provided: Finished Head

## **Part Number Info**

Part Number: AN3C4A Unpunctuated: AN3C4A NSN: 5306-00-150-9528

NIIN: 1509528

**New Surplus:** These parts are classified as new and unused, meaning they have not been installed or placed into service. However, they come without traceability or original manufacturer certifications, which might be required for certain high-level regulatory uses. Our company provides its own Certificate of Conformance (CoC) as a statement of assurance that the parts are in good working condition and have been sourced from reliable channels. These are ideal when the focus is on cost-effectiveness without compromising on quality.

**Sold Per Each:** This item is sold individually, with the price listed for a single unit. Perfect for purchasing the exact quantity needed without the requirement to buy in bulk. For larger quantities, consider reviewing any available bulk pricing options.

**Alternate Part Numbers:** Due to the nature of ever-evolving part numbering structure, multiple part numbers may meet the same specifications and performance standards. If only an alternate part number is available, we will contact you to confirm compatibility. We strongly recommend consulting the appropriate repair manuals to ensure accuracy before using an alternate part.

**Date** 2025/05/20 **Meta Fields** 

Regular Price: 11.49 Stock: 485